



# WORLD INTELLECTUAL PROPERTY ORGANIZATION



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4:

G07D 3/14, 9/06, A63F 5/00

(11) International Publication Number:

WO 88/01082

A1

(43) International Publication Date: 11 February 1988 (11.02.88)

(21) International Application Number:

PCT/GB87/00553

(22) International Filing Date:

3 August 1987 (03.08.87)

(31) Priority Application Number:

8618927

(32) Priority Date:

2 August 1986 (02.08.86)

(33) Priority Country:

GB

(71)(72) Applicant and Inventor: DUNCAN, William, Robert, Burley [GB/GB]; 97 Henderland Road, Bearsden, Glasgow G61 1JD (GB).

(74) Agent: FITZPATRICKS; 4 West Regent Street, Glasgow G2 1RS (GB).


(81) Designated States: AT (European patent), AU, BE (European patent), CH (European patent), DE (European patent), FR (European patent), GB (European patent), IT (European patent), LU (European patent), NL (European patent), SE (European patent), US.

#### Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: SORTING COINS, TOKENS AND THE LIKE



(57) Abstract

Tokens (10) passing along a track (12) are distinguished by means known per se for ejection from the track (12) at appropriate locations. At each location is provided a mechanism for forming a stack (37) of tokens and depositing the stack (37) on the surface of a table (32). Said mechanism includes a stack holder (26) which receives tokens from above, and means (34) for moving the stack holder (26) into a predetermined relationship with the table (32).

# FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	· FR	France	ML	Mali
AU	Australia	GA	Gabon	MR	Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	NL	Netherlands
BG	Bulgaria	IT	Italy	NO	Norway
BJ	Benin	JР	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
DE	Germany, Federal Republic of	LU	Luxembourg	TG	Togo
DK	Denmark	MC	Мопасо	US	United States o
FI	Finland	MG	Madagascar		
			-		

#### Sorting Coins, Tokens and the like

This invention related to the sorting of coins, tokens gaming chips and similar planar articles which are distinguished by size and/or shape and/or colour. The invention will be described hereinafter with particular reference to roulette, but it will be appreciated that other applications are equally possible.

In playing roulette it is conventional to use discshaped chips of equal size but of differing colours denoting
different players. It is necessary for the chips to be
sorted by colour after use and the sorted chips are
conventionally stacked in stacks of 20 on the table. There
is known (see British Patent Number 1 571 219) an apparatus
for sorting chips automatically by colour. This known
apparatus is positioned substantially under the gaming table
and the sorted chips are presented in stacks which are fed
upwardly in guides which project above the surface of the
table and from which the croupier must remove groups of
twenty chips and place them on the table.

One object of the present invention is to provide an improved sorting apparatus in which stacks of chips or the like are automatically fed onto the surface of a table or the like.

In known forms of roulette table it is necessary for the croupier to remove chips from the "layout" on which bets are placed by means of a rake. In the case of the prior art apparatus referred to above the non-winning chips can be raked into a chute for automatic sorting. A further object of the present invention is to enable the clearing of the chips to be performed more quickly.

Accordingly the present invention in one aspect provides an apparatus for sorting coins, tokens, chips or the like (hereinafter for convenience referred to as "chips"), comprising a hopper for receiving mixed chips, endless conveyor means arranged to receive chips one-by-one from hopper, discrimination means adapted to produce a signal identifying the value of each chip passing along the conveyor, and a plurality of means for forming chips into stacks, each such means comprising an ejector mechanism responsive to a signal from the discrimination means for ejecting a chip from the conveyor as the chip passes the ejector mechanism to fall into a stack holder arranged to receive ejected chips and form then into a stack, means for determining when the stack reaches a predetermined level, and a displacement device responsive to the determining means to cooperate with the stack holder to position the latter on a table top or similar planar surface and then withdraw the stack holder from the stack of chips.

In one form the stack holders are mounted on respective arms positioned under the table surface and the displacement device is operable to pivot the respective arm through a slot in the table to position the stack level with the table surface, a detent being provided to retain the stack on the table surface. In another form each stack holder is vertical having its bottom aligned with the table surface, and the displacement device is operable to push the stack holder forward onto the table surface.

The discrimination means may comprise an optical/electronic arrangement for discriminating chips by colour, or an electronic or mechanical arrangement for discriminating by size or weight. Such means are well known in principle to those skilled in the art.

From another aspect the present invention provides a gaming table having a playing surface bearing a layout on which chips are placed to indicate bets at predetermined odds, the playing surface in the area of the layout comprising at least one movable surface portion operable to deposit chips thereon into a hopper below the table.

In one form, a respective movable surface portion is provided for each bet possible on the layout, and means are provided for selective operation of the movable surface portions to remove the chips corresponding to losing bets at the end of a game.

Embodiments of the invention will now be described by way of example only with reference to the accompanying drawings in which:

Fig 1 is a diagrammatic side view of part of one apparatus embodying the invention,

Fig 2 is a similar view of an alternative embodiment,

Fig 3 is a plan view of part of Fig 2,

Fig 4 is a diagrammatic cross-section of a grooved guide which may be used when the mechanisms of Figures 1 to 3,

Fig 5 is a diagrammatic isometric view of an apparatus incorporating the mechanism of Fig 1,

Fig 6 is a side view, partly in section, of another alternative stacking arrangement,

Fig 7 is a plan view, to an enlarged scale, of part of Fig 6 and,

Fig 8 is a plan view of part of a roulette table incorporating the invention.

Referring to Fig 1, a chip 10 is shown in a chip carrier 12 mounted on a chain 14 which forms part of an endless conveyor known per se. The apparatus includes a plurality of stack-forming stations, one of which is seen in Fig 1, one for each colour of chip. In the following description of Fig 1, it will be understood that the other stack-forming stations are identical.

An ejector mechanism comprises a solenoid 16 whose armature carries a washer 18. On actuation of the solenoid 16, the washer 18 is moved to the position shown in broken lines, causing a pin 20 to slide in the chain 14 against the bias of spring 22. This movement of the pin 20 throws the chip 10 clear of the chip carrier 12 to fall through a guide 24 into a stack holder 26. The stack holder 26, which will be described in greater detail below, is mounted on the end of an arm 28 which is pivotally mounted at 30 below the edge of a table 32. When the stack holder is full with a predetermined number of chips eg. twenty, the arm 28 is pivoted upwardly by means such as a pivoted solenoid 34 or an electric motor or cam to align the stack holder 26 with the surface of the table 32. A sprung detent 36 retains the chips in a stack 37 on the table while the solenoid 34 returns the arm 28 and stack holder 26 to the position shown.

Figs 2 and 3 show an alternative mechanism in which the parts 10, 12, 14, 16, 18, 20 and 22 are the same. A Stack holder 26'is sliding reciprocable on the table 32' by means of solenoid 34', or equivalent means such as a motor or cam. When the stack has been formed in the holder 26', it is moved forward by the solenoid 34' and the holder 25' withdrawn.

As seen in Fig 3, the stack holder 26' may suitably be formed by half-cylindrical member 26a, 26b hinged together at 26c. The members 26a, 26b are biased towards an open position by spring 26d, but in the chip-catching condition shown are held shut by rails 38. A similar arrangement may be used for the stack holder 26 of Fig 1. Alternatively, the member 26a, 26b could be biased shut and opened by a cam.

The table surface is suitably provided with grooves indicated in Fig 3 and shown in cross-section in Fig 4. The bottom chip rests on a surface 40 and is guided by shoulder 42, thus allowing a row of stacks to be built up and pushed forward. A central slot 44 enables a user's finger to be inserted beneath a stack to assist in lifting it.

It will be understood that chips are picked up one-byone in the carriers 12 from a hopper or the like, and pass
through a discrimination means known per se. For example,
for roulette chips the discrimination means will typically
operate by illuminating the chips with white light and
passing them under a series of photodetectors each provided
with a colour filter to produce a signal identifying the
colour of each chip in the sequence. These signals are then
used to actuate the appropriate solenoid as a give chip
passes it. In the present embodiments, the stack holder is
not available to receive chips while it is engaged in
placing a completed stack on the table surface; the related
ejection solenoid is disabled during this operation, and any
chip of that colour arriving is simply recycled.

Fig 5 illustrates a typical shape and size for a sorter embodying the Fig 1 mechanism and its relationship to table height. This could be made as a freestanding unit which could be wheeled up to an existing table so that the flat surface 46 forms an extension of the table top. A hopper opening 48 may be provided into which chips can be raked.

Figs 6 and 7 illustrate another modified form of stacking mechanism. Chips are sorted as before by the elements 10-18. A chip when ejected falls into a stack holder 26' which is one of three such pivotally mounted on arms 60 equispaced about a shaft 62. Each stack holder 26' has a weight 64 to maintain it vertical an aperture 66 in its bottom, and a slot 68 extending along one side (see Fig 7b).

When a predetermined number (eg 20) of chips has been stacked in a stack holder 26', the shaft 62 is rotated to swing the stack holder 26' in an arc past an edge of the table surface 40, which is provided with ribs 42 and groove 44 as before. A finger assembly 70 is biased outwardly from the table edge by spring 72. The arrangement is such that the finger assembly passes through the aperture 66 as the holder 26' reaches it to engage the bottom of the stack. Further arcuate movement of the arm 60 causes the stack to be pushed out of the holder 26' onto the surface 40 by the rear face of the holder 26'.

Thus, the mechanism of Figs 6 and 7 again provides a means of forming stacks of chips and placing these on the surface of a gaming table (or a surface contiguous therewith).

A further aspect of the invention will now be described. In roulette, for example, a "layout" of standard format is provided for placing bets. This conventionally consists of a grid-like pattern defining square and rectangular boxes. Bets may be placed by positioning chips within a box (gambling on the result defined by that box occuring), on a line (gambling on the result defined by the two adjacent boxes), or on an intersection of lines (gambling on the result defined by the four adjacent boxes). Clearing the table of winning and losing bets at the end of a game is a time-consuming operation.

Referring to Fig 8, part of a roulette layout is shown. Instead of simple lines, the boxes 50 are divided by areas 52 whose width is approximately that of a chip 10, and thus intersections 54 capable of accommodating a chip (or stack of chips) are formed. Each part 50, 52, 54 of the table surface is formed by a hinged element which can be pivoted down, trapdoor style, to deposit the chips thereon into a hopper or conveyor for sorting as described above. The sections 50-54 can suitably be actuated by solenoids or pneumatic actuators controlled by a central computer or

other means. Thus, it would be possible to enter a winning number by keyboard and automatically remove all losing bets simultaneously, since the possible winning positions for any given number could readily be stored in memory.

This aspect of the invention also contemplates less comprehensive but still useful chip-removing arrangements. For example, the whole layout could be arranged on a single pivoted element whereby winning bets could be settled and then all remaining chips dumped.

Although the invention has been described with particular reference to roulette, it may also be applied to other subjects, eg sorting coins and placing them in stacks of predetermined quantity on a bank counter or the like.

#### CLAIMS

- Apparatus for sorting chips (as hereinbefore defined), 1... comprising a hopper for receiving mixed chips, endless conveyor means arranged to receive chips one-by-one from hopper, discrimination means adapated to produce a signal identifying the value of each chip passing along the conveyor, and a plurality of means for 5 forming chips into stacks, each such means comprising an ejector mechanism responsive to a signal from the discrimination means for ejecting a chip from the conveyor as the chip passes the ejector mechanism to fall into a stack holder arranged to receive ejected chips and form them into a stack, means for determining when the stack reaches a predetermined level, and a displacement device responsive to the determining means to cooperate with the stack holder to position the latter on a table top or similar planar surface and then withdraw the stack holder from the stack 15 of chips.
- 2. The apparatus of claim 1, in which the stack holders are mounted on respective arms positioned under the table surface and the displacement device is operable to pivot the respective arm through a slot in the table to position the stack level with the table surface, a detent being provided to retain the stack on the table surface.
- 3. The apparatus of claim 1, in which each stack holder is vertical having its bottom aligned with the table surface, and the displacement device is operable to push the stack holder forward onto the table surface.
  - 4. The apparatus of any preceding claim, in which the discrimination means comprises an optical/electronic arrangement for discriminating chips by colour, or an electronic or mechanical arrangement for discriminating by size or weight.
- 30 5. A gaming table having a playing surface bearing a layout on which chips are placed to indicate bets at predetermined odds, the playing surface in the area of the layout comprising at least one movable surface portion operable to deposit chips thereon into a hopper below the table.
- 35 6. The table of claim 5, in which a respective movable surface

portion is provided for each bet possible on the layout, and means are provided for selective operation of the movable surface portions to remove the chips corresponding to losing bets at the end of a game.

7. A gaming table according to claim 5 or claim 6, in combination with sorting apparatus according to any of claims 1 to 4.








Fig. 1










5/6






Fig. 7b

6/6




Fig. 8

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 87/00553

1. CLASSIFICATION OF SUBJECT MATTER (it several classification symbols apply, indicate all) 4							
According to International Patent Classification (IPC) or to both National Classification and IPC							
IPC <sup>4</sup> :	G 07 D 3/14; G 07 D 9/0	6; A 63 F 5/00					
II. FIELDS SEARCHED							
Minimum Documentation Searched 7							
Classificat	ion System	Classification Symbols					
	G 07 D						
IPC <sup>4</sup>	G 07 F A 63 F						
	Documentation Searched other to the Extent that such Document	than Minimum Documentation s are included in the Fields Searched *					
to the Extent that such Documents are included in the Fields Searched							
III. DOCI	JMENTS CONSIDERED TO BE RELEVANT						
Category *	Citation of Document, 11 with Indication, where ap	propriate, of the relevant passages 12	Relevant to Claim No. 13				
Y	GB, A, 1571219 (B. KNUTSS see claims; figures	SON) 9 July 1980	1				
A	cited in the application		4				
Λ.	Citca in the application		*				
Y	us, A, 3152597 (R.C. RAU) see figures; column 1 column 4, line 65 - c	l, lines 44-66;	1				
X A	FR, A, 1003486 (J. VILLARD) 18 March 1952 see abstract; figures 5-7						
			-,-				
P,A	GB, A, 2174228 (D.L. MORLEY) 29 October 1986 see abstract; figure 1; page 1, lines 1,4 5-24, 93-126						
Α	DE, C, 801257 (G. CHLESTI	L) 6 October 1952	N D				
l							
		•	D				
* Special categories of cited documents; 10							
"A" doc	ument defining the general state of the art which is not sidered to be of particular relevance.	cited to understand the principle	or theory underlying the				
"E" earlier document but published on or after the international							
filing date  "L" document which may throw doubts on priority claim(s) or  "L" document which may throw doubts on priority claim(s) or  Involve an inventive step							
which is cited to establish the publication date of another "Y" document of particular relevance; the claimed invention							
"O" doc	"O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but						
tater than the priority date claimed "A" document member of the same patent family							
IV. CERTIFICATION							
Date of the Actual Completion of the International Search  Date of Mailing of this International Search Report							
19th November 1987 19th DEC 1987							
International Searching Authority Signature of Authorized Officer							
	EUROPEAN PATENT OFFICE	M. YAN MOL	2001				

#### ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

GB 8700553

SA 18181

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 30/11/87

The European Patent Office is is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date		family ber(s)	Publication date
GB-A- 1571219	09-07-80	FR-A, B US-A- GB-A- SE-A- SE-B-	2392732 4157139 1571220 7614608 410531	29-12-78 05-06-79 09-07-80 29-06-78 15-10-79
US-A- 3152597		None		
FR-A- 1003486		None	-	
GB-A- 2174228	29-10-86	None		
DE-C- 801257	·	None		

# This Page is inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

# BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

	BLACK BORDERS
	IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
	FADED TEXT OR DRAWING
	BLURED OR ILLEGIBLE TEXT OR DRAWING
	SKEWED/SLANTED IMAGES
	COLORED OR BLACK AND WHITE PHOTOGRAPHS
	GRAY SCALE DOCUMENTS
Ö	LINES OR MARKS ON ORIGINAL DOCUMENT
	REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
0	OTHER:

IMAGES ARE BEST AVAILABLE COPY.
As rescanning documents will not correct images problems checked, please do not report the problems to the IFW Image Problem Mailbox